



▶ 1" STRUCTURAL ▶ 1" U.S. ▶ 3/4" NONSTRUCTURAL ▶ STOCKING 16', 18' AND 20' LENGTHS

Ply-Trim® Stair Stringer Components

- ▶ 100% USABLE MATERIAL
- ▶ COST EFFECTIVE SOLUTIONS – STRAIGHT TRUCKS OF DESIRED LENGTHS, RANDOM TALLIES AVAILABLE (BETTER INVENTORY CONTROL)
- ▶ CNC MACHINE READY
- ▶ UNIFORM THICKNESS



Technical Specifications

THICKNESS:	3/4" NONSTRUCTURAL, 1" U.S. AND 1" STRUCTURAL
STANDARD FINISH:	PRIME COATED – 4 SIDES
STANDARD DEPTHS:	9-1/4" AND 11-1/4"
STANDARD LENGTHS:	16', 18' AND 20'
SPECIAL ORDERS:	UPON REQUEST – CALL FOR QUOTE

Engineering Specifications – ASTM – D198

STATIC BENDING – EDGE (BEAM) – F_b	= 4,100 PSI
COMPRESSION SHORT MEMBER	= 2,500 PSI
COMPRESSION LONG MEMBER	= 3,000 PSI

Stair Stringer Physical & Packaging Specifications

SIZE	WEIGHT/ LIN. FT.	APPROX. WEIGHT PER UNIT/ 16' LENGTH	PIECES PER UNIT
3/4" x 9-1/4" (7 PLY)	1.45 lbs.	2320 lbs.	105
3/4" x 11-1/4" (7 PLY)	1.97 lbs.	2648 lbs.	84
1" x 9-1/4" (10 PLY) SS	2.28 lbs.	2736 lbs.	75
1" x 11-1/4" (10 PLY) SS	2.78 lbs.	2669 lbs.	60
1" x 9-1/4" U.S.	2.32 lbs.	2785 lbs.	75
1" x 11-1/4" U.S.	2.60 lbs.	2808 lbs.	60



PLY-TRIM, INC.

550 N. Meridian Road, Youngstown, OH 44509
 1-800-PLY-TRIM • 330-799-7876 • Fax: 330-799-2908
www.plytrim.com

PLY-TRIM WEST, INC.

2920 S. Cushman Drive, Tacoma, WA 98409
 1-800-545-4454 • 253-572-7300 • Fax 253-272-5270
www.ply-trimwest.com